

DECLARATION OF PERFORMANCE

1071-CPR-7027

S22NW



1. Product Type:

2. Product Batch:

batch information shown on label

3. Intended uses:

Intended for	Harmonized Technical Specification	Functions
Roads and other trafficked areas	EN 13249:2016	Filtration, Separation, Reinforcement
Railways	EN 13250:2016	Filtration, Separation, Reinforcement
Earthworks, foundations and retaining structures	EN 13251:2016	Filtration, Separation, Reinforcement
Drainage control	EN 13252:2016	Filtration, Separation, Drainage
Erosion control works	EN 13253:2016	Filtration, Separation, Reinforcement
Reservoirs and dams	EN 13254:2016	Filtration, Separation, Reinforcement
Canals	EN 13255:2016	Filtration, Separation, Reinforcement
Solid waste disposals	EN 13257:2016	Filtration, Separation, Reinforcement
Liquid waste containments	EN 13265:2016	Filtration, Reinforcement

4. Manufacturer:

THRACE NONWOVENS & GEOSYNTHETICS S.A.

5. Address:

Magiko, 671 00, Xanthi, Greece
Tel: +30 210 9875038-50, e-mail: geo@thraceplastics.gr

6. AVCP System:

System 2+

Last two digits of the year of affixing CE marking:

09

7. **SINTEF AS** (Notified Body 1071) performed the initial inspection of the manufacturing plant and of factory production control (FPC) and the continuous surveillance, assessment, and evaluation of the FPC and issued the certificate of factory production control.

8. Declared performance:

Essential Characteristics	Declared Performance				Harmonized Technical Specification
	Declared Value	Tolerance	Unit	Test Standard	
Tensile Strength T_{max} (MD/CD)	22/22	-3/-3	kN/m	EN ISO 10319	EN 13249:2016 EN 13250:2016 EN 13251:2016 EN 13252:2016 EN 13253:2016 EN 13254:2016 EN 13255:2016 EN 13257:2016 EN 13265:2016
Elongation ϵ_{max} (MD/CD)	45/55	$\pm 10.4/\pm 12.7$	%	EN ISO 10319	
Resistance to static puncture F_p (CBR)	3.7	-0.555	kN	EN ISO 12236	
Dynamic puncture resistance (cone drop test)	14	+4	mm	EN ISO 13433	
Characteristic Opening Size (O_{90})	70	± 21	μm	EN ISO 12956	
Water permeability (q_N)	75	-22	$l/(m^2s)$	EN ISO 11058	
Water flow capacity in the plane	1.6	-0.5	$10^{-6} m^2/s$	EN ISO 12958	
Durability (Annex B)	To be covered within two weeks after installation. Predicted to be durable for up to 100 years in natural soils with $4 \leq pH \leq 9$ and soil temperatures $\leq 25^\circ C$.				
Dangerous substances (National regulations valid in the EU member states)	Less than required by national regulations in EU member states				

10. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer:

Konstantinos Emmanouil
Quality Assurance Manager

Magiko, 2025-05-19

THRACE NONWOVENS & GEOSYNTHETICS S.A.

Magiko Xanthi, 67100, Xanthi, Greece, T +30 25410 45675-6 | F +30 25410 45677
www.thracegroup.com